



VERSOSB115P

The VERSOSB115P is the self-powered subwoofer reinforcement unit of the VERSO series. Its compact design is ideal for those musical mobile applications where you need an extra punch at the low-end side of the audible spectrum.

Key features

- 15" driver
- 500 W RMS integrated amplifier
- XLR inputs with mono conversion
- XLR stack outputs (link to other SB115P units, VERSO P speakers, etc.)
- PHASE and volume controls
- Internal 100 or 150 Hz LPF (selectable)
- Top-hat 35 mm. standard pole mount socket
- Optional wheel kit (QRA + WH200 KIT)



VERSO AND VERSOP ACCESSORIES



SR8



SR12

BAGVERS08, BAGVERS010, BAGVERS012



CNX2RCA XLR2

CNXRCA XLR2

CNX XLR XLR 1M5/5/10/20

Audio signal connections

High quality pre made audio connections complete the Verso versatility:

- **CNX2RCA XLR2**: 2 x RCA (stereo) - 1 x XLRM 2 m wire
- **CNXRCA XLR2**: RCA - XLRM 2 m wire
- **CNX XLR XLR**: 1M5 / 5 / 10 / 20: XLRM - XLRM 1.5, 5, 10, 20 m wire

XLR - XLR cables are available in four different wire lengths: 1.5, 5, 10 and 20 m. All connections use OFC and PVC protective jacket. Stereo to mono connections include internal resistors for load protection and proper audio signal addition.

Transportation bags

- **BAGVERS08, BAGVERS010, BAGVERS012**: bag for easy transportation and storage

Wall brackets and tripod mounting

- **SR8**: wall support for VERSO8, VERSO8P, VERSO10, VERSO10P
- **SR12**: wall support for VERSO10, VERSO10P, VERSO12, VERSO12P

Technical Characteristics

VERSOSB115P

System	Bass active cabinet
Driver	15" x1
Power output (RMS)	500W
Maximum SPL (dB@1m)	125dB
Inputs sensitivity nom/impedance	0dBV 1V 20kΩ [Balanced]
Input connector type	XLR3 balanced
Stack connector type	XLR3 balanced
Frequency response [-3dB]	35Hz-100Hz / 35Hz-150Hz
THD + Noise @ 1kHz Full power	<1%
Low pass filter 12dB/oct.	100Hz / 150Hz
Indicators:	
Signal present	-40dBV
Clip	
Mains	AC 115V/230V* 50-60Hz
Power consumption	250VA
(pink noise, 1/8 power)	440VA
(pink noise, 1/3 power)	
Dimension (WxDxH) (without accessories)	590x490x450mm
Net weight	41.3kg